

TK Oak Capri

TK Oak Capri

TK Oak Capri is a unique and elegant wooden floor with a natural and dynamic expression. Each board is individually handmade in our own production facility in Europe. TK Oak Capri can be laid as a plank floor, a classic Italian herringbone or in a chevron pattern.

Trækompagniet

When you buy a wooden floor at Trækompagniet, you get a very experienced partner along on your floor journey. We are involved in the entire process, from design and production to when the floor needs to be installed in your home.

Inspiration

Our Icelandic roots has led us to seek inspiration from the magnificent volcanic landscape and nature of Iceland.

Our Concept



Natural colour changes

All Trækompagniet floors are natural products which will over time change colour depending on sun exposure and wear. Typically, light floors will become lighter while dark floors will become darker. This change is mostly noticeable in the first six months after installation.

| Product information | | |
|---------------------|---------------------------------------|--|
| Raw material top | European Oak | |
| Raw material base | Birch plywood | |
| Surface | Brushed | |
| Initial treatment | None. Comes treated with hard wax oil | |
| Installation | Glued down | |

<u>Underfloor heating</u>

TK Oak Capri is especially well suited for underfloor heating systems due to its layered structure. The layers prevent the wood from expanding and contracting as a result of seasonal adjustments in temperature and humidity.

Regular care and maintenance

Trækompagniet's own care and maintenance products are especially suitable for caring and maintaining each of our floors. This applies to both flooring soaps containing floor wax for cleaning the floors, as well as maintenance oils, which help maintain the floor's unique sturdy finish.

Further information

traekompagniet.com



Technical Data

| Plank | Herringbone | Chevron |
|---|--|--|
| Width (mm) | Width (mm) | Width (mm) |
| 140 / 180 / 220 / 260 | 100 / 120 / 150 | 100 / 120 / 150 |
| Varied Lengths (mm) | Length (mm) | Length (mm) |
| 800 - 2400 | 600 / 730 / 1000 | 520 / 640 / 920 |
| Thickness (mm) | Thickness (mm) | Thickness (mm) |
| 16 / 21 / 30 | 16 | 16 |
| Top layer thickness (mm) | Top layer thickness (mm) | Top layer thickness (mm) |
| 4 / 6 | 4 | 4 |
| Treatment | Treatment | Treatment |
| Hard wax oil | Hard wax oil | Hard wax oil |
| Layered structure | Layered structure | Layered structure |
| Grading | Grading | Grading |
| Nature ¹ / Knotty ² | Nature ¹ /Knotty ² | Nature ¹ /Knotty ² |
| Edge | Edge | Edge |
| Bevelled | Bevelled | Bevelled |

Note* Some combination may not be possible to combine.

¹ Nature – Few filled knots may occur ² Knotty – Filled knots occur