

## TK Oak Vulcano Fox


### TK Oak Vulcano Fox

TK Oak Vulcano Fox is a well-established member in the popular Vulcano-series. The floor has an outstanding glow with a colour shade rarely seen elsewhere. All Vulcano floors are heat treated and each board is handmade in our own production facility in Europe. The brushed surface gives the floor a robust and rustic look.

TK Oak Vulcano Fox comes treated with hard wax oil from the production, which makes the floor particularly robust and requires minimum maintenance.

### Inspiration

Our Icelandic roots has led us to seek inspiration from the magnificent volcanic landscape and nature of Iceland. The dark shade in TK Oak Vulcano Fox is inspired by Reynisfjara Black Beach located in the south of



### Underfloor heating

TK Oak Vulcano Fox is especially well suited for underfloor heating systems due to its layered structure. The layers prevent the wood from expanding and contracting as a result of seasonal adjustments in temperature and humidity.







### Regular care and maintenance

Trækompagniet's own care and maintenance products are especially suitable for caring and maintaining each of our floors. This applies to both flooring soaps containing floor wax for cleaning the floors, as well as maintenance oils, which help maintain the floor's unique sturdy finish.

### Further information

[traekompagniet.com](http://traekompagniet.com)

## Technical Data

Plank 	Herringbone 	Chevron 
Width (mm) 140 / 180 / 220 / 260	Width (mm) 100 / 120 / 150	Width (mm) 100 / 120 / 150
Varied Lengths (mm) 800 - 2400	Length (mm) 600 / 730 / 1000	Length (mm) 520 / 640 / 920
Thickness (mm) 16 / 21 / 30	Thickness (mm) 16	Thickness (mm) 16
Top layer thickness (mm) 4 / 6	Top layer thickness (mm) 4	Top layer thickness (mm) 4
Treatment Hard wax oil	Treatment Hard wax oil	Treatment Hard wax oil
Layered structure 	Layered structure 	Layered structure 
Grading Nature <sup>1</sup> / Knotty <sup>2</sup>	Grading Nature <sup>1</sup> / Knotty <sup>2</sup>	Grading Nature <sup>1</sup> / Knotty <sup>2</sup>
Edge Bevelled	Edge Bevelled	Edge Bevelled

Note\* Some combination may not be possible to combine.

<sup>1</sup> Nature – Few filled knots may occur


<sup>2</sup> Knotty – Filled knots occur

## Product Information

Raw material top	European Oak
Raw material base	Birch plywood
Surface	Brushed
Initial treatment	None. Comes treated with hard wax oil
Installation	Glued down



## Our Concept



### Natural colour changes

All Trækompagniet floors are natural products which will change colour over time depending on sun exposure and wear. Typically, light floors will become lighter while dark floors will become darker. This change is mostly noticeable in the first six months after installation.

### Repair and ongoing maintenance

Trækompagniet offers a wide selection of supplementary maintenance products which are especially suitable for caring and maintaining each of our floors. Professional repairment and ongoing maintenance available on request. Should one floorboard become substantially damaged, individual board replacements are possible.